


Planet Phone VIP-254T



Log in



username = root (default No password)

Enter Network Password

Enter your username and password to login
PLANET IP Phone Configuration

Username

Password

Firmware ที่ใช้งาน

PLANET
Networking & Communication

SIP Phone
Configuration Menu

Phone Book

Phone Setting

Network

SIP Settings

NAT Trans.

Others

System Auth.

Save & Reboot

System Settings

Reboot without Saving

System Information

This page illustrate the system related information.

| | |
|-------------------|--|
| Company: | PLANET Technology Corp. |
| Firmware Version: | VIP-254T/PT V1.0.3 |
| Codec Version: | Tue May 19 09:42:12 2009. (905190) |
| Contact Address: | 11F, No. 96, Min Chuan Road, Hsin Tien, Taipei, Taiwan, R.O.C |
| Tel: | 886-2-22199518 |
| Fax: | 888-2-22199528 |
| E-Mail: | support_voip@planet.com.tw |
| Web Site: | www.planet.com.tw |

การ config account cat2call+

The screenshot shows a web browser window with the URL `192.168.1.201/login.cgi`. The page title is "Service Domain Settings". A red box highlights the "Service Domain Settings" title. Below the title, there is a dropdown menu for "Realm No." set to "Realm 1". A table with a blue header "Realm" contains the following settings:


| Realm | |
|--------------------|---|
| Active: | <input checked="" type="radio"/> On <input type="radio"/> Off |
| Display Name: | 021053006 |
| User Name: | +6621053006 |
| Register Name: | 6621053006@catnextgen.com |
| Register Password: | |
| Domain Server: | catnextgen.com |
| Proxy Server: | 202.129.61.102 |
| Outbound Proxy: | 202.129.61.102 |
| Subscribe for MWI: | <input type="radio"/> On <input checked="" type="radio"/> Off |
| Status: | Registered |

At the bottom of the form, there are "Submit" and "Reset" buttons. A red box also highlights the "Active" field and the "Status" field.

On the left side, there is a navigation menu with the following items:

- Phone Book
- Phone Setting
- Network
- SIP Settings**
- NAT Trans.
- Others
- System Auth.
- Save & Reboot
- System Settings
- Reboot without Saving

Port setting



SIP Phone Configuration Menu

- Phone Book >
- Phone Setting >**
- Network >
- SIP Settings >
- NAT Trans. >
- Others >
- System Auth. >
- Save & Reboot >
- System Settings >
- Reboot without Saving >

Port Settings

You could set the port number in this page.

| | | |
|-----------------|---|---|
| SIP Port: | <input type="text" value="5060"/> | (0~65533) (Set 0 for auto, range as bellow) |
| RTP Port: | <input type="text" value="20000"/> | (0~65533) (Set 0 for auto, range as bellow) |
| SIP Port Range: | <input type="text" value="10000"/> ~ <input type="text" value="10999"/> | (1024~40000) |
| RTP Port Range: | <input type="text" value="20000"/> ~ <input type="text" value="21999"/> | (1024~40000) |

Set codec



SIP Phone Configuration Menu

- Phone Book
- Phone Setting
- Network
- SIP Settings**
- NAT Trans.
- Others
- System Auth.
- Save & Reboot
- System Settings
- Reboot without Saving

Codec Settings

You could set the codec settings in this page.

| Codec Priority | |
|-------------------|-------------|
| Codec Priority 1: | G.729 |
| Codec Priority 2: | G.711 a-law |
| Codec Priority 3: | G.723 |
| Codec Priority 4: | Not Used |
| Codec Priority 5: | Not Used |
| Codec Priority 6: | Not Used |
| Codec Priority 7: | Not Used |
| Codec Priority 8: | Not Used |
| Codec Priority 9: | Not Used |

| RTP Packet Length | |
|-------------------|-------|
| G.711 & G.729: | 20 ms |
| G.723: | 30 ms |

| G.723 5.3K | |
|-------------|---|
| G.723 5.3K: | <input type="radio"/> On <input checked="" type="radio"/> Off |

| Voice VAD | |
|------------|---|
| Voice VAD: | <input type="radio"/> On <input checked="" type="radio"/> Off |

Set DTMF



DTMF Setting

You could set the DTMF setting in this page.

RFC 2833

Inband DTMF

Send DTMF SIP Info

Set Register Expire Time

PLANET
Networking & Communication

SIP Phone
Configuration Menu

- Phone Book
- Phone Setting
- Network
- SIP Settings**
- NAT Trans.
- Others
- System Auth.
- Save & Reboot
- System Settings
- Reboot without Saving

Other Settings

You could set other settings in this page.

| | |
|--------------------------|---|
| Hold by RFC: | <input type="radio"/> On <input checked="" type="radio"/> Off |
| Voice QoS (Diff-Serv): | 40 (0~63) |
| SIP QoS (Diff-Serv): | 40 (0~63) |
| SIP Expire Time: | 60 (15~86400 sec, 0=define by Server) |
| Use DNS SRV: | <input type="radio"/> On <input checked="" type="radio"/> Off |
| Send Keep Alives Packet: | <input type="radio"/> On <input checked="" type="radio"/> Off |
| Keep Alives Period: | 60 (15~250 sec) |
| Jitter Buffer: | 1 (0~32 packets) |
| SIP Server type: | General |
| SIP VID (VLAN): | 0 (2~4094, 0:disabled) |
| RTP VID (VLAN): | 0 (2~4094, 0:disabled) |

Save config



SIP Phone Configuration Menu

- Phone Book >
- Phone Setting >
- Network >
- SIP Settings >
- NAT Trans. >
- Others >
- System Auth. >
- Save & Reboot**
- System Settings >
- Reboot without Saving

Save & Reboot

You have to save changes to effect them.

Save Changes:



ESET Smart Security
ESET Smart Security requires your attention. For more information, click on this notification.